

Operation Manual

Obtek 13" ***Oscillating Pad Machine***

**PLEASE READ this manual thoroughly
before you run the Obtek.**

The **Orbtek** has been designed for the agitation of pre-sprays, low moisture encapsulation cleaning and polishing of hard surfaces. Ideally suited for use in the domestic cleaning sector, it's lightweight, powerful and manoeuvrable. At 13kg, it requires very little effort to use.

Technical Specifications

Model	Power	Voltage	Amplitude	Weight	Pad diameter	Length of cable
WOC03	350W	220V	1440RPM/min	14kg/15kg	13"	6m

Electrical Safety

- The power socket used must be earthed, use of an RCD is heavily advised, do not change or modify the plug as this will invalidate the guarantee.
- Do not store the machine in a moist or wet environment, this can increase the risk of earth leakage, corrosion and electric shock.
- Damage or entangled wires may increase the risk of electrical shock when in use.
- Make sure the switch is off before plugging in the power cord.
- Do not put excessive pressure on the machine during use, this can cause damage to its components/motor due to excessive load upon the components, brush head and drive assembly.
- Check the machine on a regular basis for damage. Including the cable, plug, switch and handle assembly.

Precautions

- The floor pads/brushes need to be attached to the machine before it can be used.
- Always store the machine on the white transport pad (supplied) or a red or black 3M style pad.
- Never store on the machine sat on the brushes, this can damage the brush pattern and the drive board.

Assembly Instructions

1. Remove the screw and bolt assemblies, slide the two tubes of the handle assembly together, then tighten the two internal hexagon screws securely to build the handle.



2. Connect the handle power lead to the motor power socket.



3. Tilt the machine on its back and attach the brush, stripping pad or microfiber pad to the Velcro base.



4. Press down on the black handwheel continuously while adjusting the height of the operating handle.



5. Plug the mains cable into the power, press and use the switch to turn on and off.



6. Attach the water tank to the handlebar tube and connect the silicone pipe through the rear of the machine base.



1. ON/OFF switch.
2. Tee handle.
3. Solution feed dial.
4. Solution tank.
5. Transport wheels.
6. Chassis base.
7. Drive motor.
8. Handle release adjustment.



Solution World of Clean Ltd

Unit 1, Indian Queens Industrial Estate,

Warren Rd,

Indian Queens,

St Columb,

TR9 6TL

www.worldofclean.co.uk